

AmSqueeze RS 516 A24-A93 2840x260x16mm

Article code: EWMS000401

General information

Product group	endless woven
Industry segment	Food: Meat & poultry
Main product feature	Foodgrade, Abrasion resistant, Oil & grease resistant, Cut resistant
Application	Soft Separator

Belt construction

Tension layer		polyester/aramid
Number of plies		1
Top side	material	Ropanyl, TPU
	finish	profile, A93-Rhombus
	color	white
Bottom side	material	Ropanyl, TPU
	finish	profile, A24 Herringbone profile
	color	white

Characteristics

Food Grade (FG)	yes	EC 1935/2004, EU 10-2011; FDA
Antistatic (AS)	no	
Flame-retardant (FR)	no	

Technical data

Hardness	ISO 868	top side	85A Shore		
		bottom side	85A Shore		
Force at 1% elongation	ISO 21181		39 N/mm	222.7	lbs/in.
Thickness		total	16 mm	0.63	in.
		top cover	6.7 mm	0.26	in.
		bottom cover	6.7 mm	0.26	in.
Weight			26.0 kg/m ²	5.33	lbs/ft ²
Length		from / to	2840 mm		in.
Width		from / to	260 mm		in.
Operating temperature	continuous	from / to	-20 / 90 °C	-4 / 194	°F
	short	from / to	-30 / 110 °C	-22 / 230	°F
Minimum pulley diameter			160 mm	6.3	in.

Tolerances

Length	± 1 %	minimum ±	20 mm	0.79	in.
Width		from / to	-1 / +1 mm	-0.04 / +0.04	in.
Thickness		±	0.2 mm	0.01	in.