



Slat Top Plastic Chain

Series **uni 882** Type **Magnetic**



Slat Top Plastic Chain

Side flexing chain
Pitch: 38.1 mm (1.50 in)
Backflex radius:
40.0 mm (1.57 in)
Permissible tensile strength:
POM material:
4000 N (899 lbf)

Standard shipping lengths:
boxes of 80 links
= 3.048 m (10.0 ft)

E		G		H		L		P		Q		T	
mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in
9.3	0.36	60.0	2.36	19.0	0.75	9.5	0.37	38.1	1.50	57.0	2.24	4.8	0.19

All dimensions are for chains in POM material.


	Width (W)		Material & color		Pin material	Weight		Min. radius (R)	
	mm	in				kg/m	lb/ft	mm	in
K750	190.5	7.50	POM-DK DG	POM-LF BR	SS431	2.19	1.46	610	24.02
K1000	254.0	10.00	POM-DK DG	POM-LF BR	SS431	2.44	1.63	610	24.02
K1200	304.8	12.00	POM-DK DG	POM-LF BR	SS431	2.73	1.82	610	24.02

Non standard material and color: See uni Material and Color Overview.

Non standart pin material: See uni Material and Color Overview.


Accessories

Rubber Top



When ordering, please state the required distance between the Rubber Top.

Other Non Standard rubber profiles:
See uni Rubber Profile Overview.



Width	Link material	Rubber material	Z		X		Y	
			mm	in	mm	in	mm	in
K750	POM-LF BR	05 I	160.0	6.30	15.6	0.61	3.0	0.11
K1000	POM-LF BR	05 I	200.0	7.87	15.6	0.61	3.0	0.11
K1200	POM-LF BR	05 I	240.0	9.45	15.6	0.61	3.0	0.11

STANDARD

SIDE FLEXING

PITCH 38.1 MM/1.50 IN


Sprocket

No of teeth	Pitch diameter		Overall-diameter		Min. ø bore		Max. ø bore		Hub-diameter		Dimension A		Dimension B		Machined PA6 
	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	
Z9	111.4	4.39	112.5	4.43	25.0	0.98	40.0	1.57	62.5	2.46	60.4	2.38	67.2	2.65	✓
Z10	123.4	4.86	124.9	4.92	25.0	0.98	40.0	1.57	74.9	2.95	66.4	2.62	73.2	2.88	✓
Z11	135.2	5.32	136.4	5.37	25.0	0.98	40.0	1.57	86.4	3.40	72.3	2.85	79.1	3.11	✓
Z12	147.2	5.80	148.5	5.85	25.0	0.98	40.0	1.57	98.5	3.88	78.6	3.09	85.1	3.35	✓


Two-part sprocket

No of teeth	Pitch diameter		Overall-diameter		Min. ø bore		Max. ø bore		Hub-diameter		Dimension A		Dimension B		Molded PA6 LG 
	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	
Z9	111.4	4.39	112.5	4.43	25.0	0.98	45.0	1.77	62.5	2.46	60.4	2.38	67.2	2.65	✓
Z10	123.4	4.86	124.9	4.92	25.0	0.98	45.0	1.77	74.9	2.95	66.4	2.62	73.2	2.88	✓
Z11	135.2	5.32	136.4	5.37	25.0	0.98	45.0	1.77	86.4	3.40	72.3	2.85	79.1	3.11	✓
Z12	147.2	5.80	148.5	5.85	25.0	0.98	45.0	1.77	98.5	3.88	78.6	3.09	85.1	3.35	✓



Machined sprocket



Machined two-part sprocket



Molded two-part sprocket



Please ensure that sufficient size shaft and keyway are chosen for corresponding load.

Non standard material and color:
See uni Material and Color Overview.

Other sprocket sizes are available upon request

Width of tooth: 22.20 mm/0.87 in

Width of Machined sprocket: 42.0 mm/1.65 in

Width of Moulded sprocket: 58.5 mm/2.30 in

uni Retainer Rings: See uni Retainer Ring data sheet:

<https://app.eptool.online/downloads?query=retainer-ring>



uni 882 Magnetic / 2025.07.24



The local partner of choice for
sustainable conveyor belting solutions
– around the globe.

<http://eptool.online>

Member of Ammega Group.



Scan the QR code
and find your local
contact

Ammeraal Beltech Modular
Hjulgagervej 21
DK-7100 Vejle
T +45 7572 3100

<http://eptool.online>

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.