





Special Plastic Chain

Series **uni 882** Type **Magnetic LBP**



Special Plastic Chain

Side flexing chain
 Pitch: 38.1 mm (1.50 in)
 Backflex radius:
 150.0 mm (5.9 in)
 Permissible tensile strength:
 POM material:
 3900 N (876 lbf)
 Standard shipping lengths:
 boxes of 40 links
 = 1.524 m (5.0 ft)

E		G		H		L		P		Q		T		V	
mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in
6.8	0.27	60.0	2.36	14.2	0.56	24.0	0.94	38.1	1.50	57.0	2.24	19.3	0.76	33.5	1.32

All dimensions are for chains in POM material.

	Width (W)		Recommended base material & color	Recommended roller material & color	Recommended pin material	Weight		Min. radius (R)	
	mm	in				kg/m	lb/ft	mm	in
K750	190.5	7.50	POM-LF BR	POM-D G	SS304	5.0	3.35	610	24.02
K1000	254.0	10.00	POM-LF BR	POM-D G	SS304	6.1	4.07	610	24.02
K1200	304.8	12.00	POM-LF BR	POM-D G	SS304	6.9	4.61	610	24.02

Non standard material and color: See uni Material and Color Overview.

Non standart pin material: See uni Material and Color Overview.

STANDARD

SIDE FLEXING

PITCH 38.1 MM/1.50 IN


Sprocket

No of teeth	Pitch diameter		Overall-diameter		Min. ø bore		Max. ø bore		Hub-diameter		Dimension A		Dimension B		 Machined PA6
	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	
Z9	111.4	4.39	112.5	4.43	25.0	0.98	40.0	1.57	62.5	2.46	60.4	2.38	83.0	3.27	✓
Z10	123.4	4.86	124.9	4.92	25.0	0.98	40.0	1.57	74.9	2.95	66.4	2.62	88.4	3.48	✓
Z11	135.2	5.32	136.4	5.37	25.0	0.98	40.0	1.57	86.4	3.40	72.3	2.85	94.3	3.71	✓
Z12	147.2	5.80	148.5	5.85	25.0	0.98	40.0	1.57	98.5	3.88	78.6	3.09	100.3	3.95	✓


Two-part sprocket

No of teeth	Pitch diameter		Overall-diameter		Min. ø bore		Max. ø bore		Hub-diameter		Dimension A		Dimension B		 Molded PA6	 Machined PA6
	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in		
Z9	111.4	4.39	112.5	4.43	25.0	0.98	45.0	1.77	62.5	2.46	60.4	2.38	83.0	3.27		✓
Z10	123.4	4.86	124.9	4.92	25.0	0.98	45.0	1.77	74.9	2.95	66.4	2.62	88.4	3.48		✓
Z11	135.2	5.32	136.4	5.37	25.0	0.98	45.0	1.77	86.4	3.40	72.3	2.85	94.3	3.71		✓
Z12	147.2	5.80	148.5	5.85	25.0	0.98	45.0	1.77	98.5	3.88	78.6	3.09	100.3	3.95	✓	✓



Machined sprocket



Machined two-part sprocket



Molded two-part sprocket



Please ensure that sufficient size shaft and keyway are chosen for corresponding load.

Non standard material and color:
See uni Material and Color Overview.

Other sprocket sizes are available upon request
 Width of tooth: 22.20 mm/0.87 in
 Width of Machined sprocket: 42.0 mm/1.65 in
 Width of Moulded sprocket: 58.5 mm/2.30 in
 uni Retainer Rings: See uni Retainer Ring data sheet:
<https://app.eptool.online/downloads?query=retainer+ring>



uni 882 Tab LBP / 2025.07.06



The local partner of choice for
sustainable conveyor belting solutions
– around the globe.

<http://eptool.online>

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.

Member of Ammega Group.



Scan the QR code
and find your local
contact

Ammeraal Beltech Modular
 Hjulmagervej 21
 DK-7100 Vejle
 T +45 7572 3100

<http://eptool.online>