

# AmDough

Endless Woven Belts for Biscuit Bakeries

# Learn more about our innovations

Ammeraal Beltech knows about industrial bakeries. When the company was founded in 1950, the first belt ever produced was an Endless Woven bakery belt. Since then, we have been gathering experience and expanding our knowledge, and all of this benefits our customers.

Ammeraal Beltech is a major supplier to the food industry in general and to biscuit bakeries in particular.

The biscuit bakery industry requires high-performance and long-lasting dough handling belts. Ammeraal Beltech is a reliable supplier of both.

One basic demand in bakeries is that the dough should not stick to the conveyor or process belt. Two methods of dough forming are an exception:

- Rotary moulder
- Rotary cutter



# Bakery production


## Extraction process



Dough is pressed into a rotating moulder drum that forms the shape of the biscuits.

- The belt is squeezed between the moulding and pressure drums.
- Then the belt releases, creating a suction effect at the same time.
- Moisture and fat from the dough are absorbed into the belt so that the moulded dough sticks to the belt.
- The formed dough then travels with the belt and is extracted from the moulding drum.

## Cutting process



A rotating cutter (or knife) cuts the biscuit shape into the layer of dough.

- The layer of dough is transported over the belt.
- As the dough passes the cutting drum, the biscuit form is cut out and pressed onto the belt.
- The remaining dough around the biscuits is guided onto a separate scrap conveyor belt for re-use.
- The biscuit forms are then transferred to the oven feeding belt.

## Release process



At the end of both processes, the belt is pulled over a knife edge.

- Moisture and fat are forced to the top surface of the belt, thus forming a film.
- This effect, combined with the sharp bending and stretching of the belt over the knife edge, releases the fragile biscuit dough from the belt surface so that it can continue to the oven.




Diagram of a rotary moulder



Ammeraal Beltech  
member European  
Hygienic Engineering  
& Design Group

# How to select AmDough Endless Woven Belts

The extraction and release characteristics are determined by three main factors:

## 1. Absorption capacity

This is determined by the content and combination of materials: cotton, flax, polyamide and polyester. Cotton and flax can absorb 20 to 25% of moisture, polyamide 4% and polyester 0.4%.

*The belt with the highest absorption capacity is the AmDough 100.*

Maximum extraction performance from the moulder drum requires a high absorption factor, and best release characteristics on the knife edge transfer call for a low absorption factor. This means that an ideal balance is needed to achieve both good extraction and good release. When different dough types are processed on the same line, one of the two universal AmDough Belt types can be used.

## 2. Weave pattern

The pattern and amount of air between dough and belt influence the dough release. Plain and twill weave have a more open surface than broken twill. The weave type to be applied depends on the composition and shape of the dough.



**Broken twill weave GK**  
Equally spaced air pockets



**Twill weave K**  
Air grooves in herringbone pattern



**Plain weave P**  
Lateral air grooves

## 3. Belt thickness

A thinner belt can run over the smallest knife edge and follow its shape very closely to allow for good release of the thinnest products.

### Standard product range

Belt type	Material	Weave	Belt thickness	Diameter of knife edge < 135°	Article code	
<b>AmDough 100</b>	cotton	broken twill	2.8 mm	5 mm	GK 1283B	
<b>AmDough 90</b>	cotton	broken twill	2.4 mm	4 mm	GK 0983B	
<b>AmDough 80</b>	cotton/ polyamide	broken twill	2.4 mm	4 mm	GK 8484BP	
<b>AmDough 70</b>	cotton	plain	2.0 mm	3 mm	P 1284B	
<b>AmDough 60</b>	cotton/ polyamide	broken twill	2.4 mm	4 mm	GK 0983BP	universal type
<b>AmDough 50</b>	cotton/ polyamide	plain	1.8 mm	3 mm	P 8484BP	universal type
<b>AmDough 40</b>	cotton/ polyamide	plain	2.0 mm	3 mm	P 1284BP	
<b>AmDough 20</b>	cotton/ polyester	plain	2.0 mm	3 mm	P 4060BE	

There is a linear relationship between the AmDough absorption numbers:

**Heavy dough • wet • high degree of moisture • AmDough Belt with higher absorption factor**  
**Light dough • dry • low degree of moisture • AmDough Belt with lower absorption factor**

**Top side:** always uncoated

**Bottomside:** PUR transparent food grade impregnation for stability, better wear resistance and longer belt life

**Belt edges:** reinforced polyamide selvages

**Dimension:** length up to 100 m, width up to 3400 mm

Broken twill types (GK) are also available as Twill (K) versions.


# Why choose an Endless Woven AmDough Belt?

- **Less headache, better yield and longer life**



AmDough Belts are manufactured to high quality standards. The bottom side is impregnated with wear resistant PU to maintain the belt shape and to prevent narrowing. Cord yarns are used to increase wear resistance, and polyamide to reinforce the selvages. Strong flax yarns in the weft ensure lateral stability. As a result, their extended belt life and continuous absorption capacity make the Endless Woven AmDough Belts very cost-effective.

- **Trouble-free dough processing**



The main benefit of Endless Woven AmDough Belts is the absence of a splice or seam, thus ensuring continuous absorption and smooth product transfer. Scrapers can easily remove remnant dough without damaging the belt.

- **Consistent product quality**



AmDough Belts have consistent extraction and release properties. Biscuit tails are limited to a minimum because low drum pressure is required to get optimum demoulding. These characteristics ensure smooth biscuit transfer without any interruption or deformation of the formed dough.

- **The optimum solution for every dough type**



Endless Woven AmDough Belts are suitable for all biscuit dough types. Their components are safe and transmit no colour, taste or smell to the biscuit products. The absence of antistatic fibres means that the belts can be used in combination with metal detectors.

# Local Contacts

## Australia

T +61 3 8780 6000  
info-au@ammeraalbeltech.com  
www.ammeraalbeltech.com/au

## Austria

T +43 171728 133  
info-de@ammeraalbeltech.com  
www.ammeraalbeltech.at

## Belgium

T +32 2 466 03 00  
info-be@ammeraalbeltech.com  
www.ammeraalbeltech.com/be

## Canada

T +1 905 890 1311  
info-ca@ammeraalbeltech.com  
www.ammeraalbeltech.com/ca

## Chile

T +56 2 233 12900  
info-cl@ammeraalbeltech.com  
www.ammeraalbeltech.cl

## China

T +86 512 8287 2709  
info-cn@ammeraalbeltech.com  
www.ammeraalbeltech.com/cn

## Czech Republic

T +420 567 117 211  
info-cz@ammeraalbeltech.com  
www.ammeraalbeltech.com/cz

## Denmark

T + 45 7572 3100  
info-dk@ammeraalbeltech.com  
www.unichains.com

## Finland

T +358 207 911 400  
info-fi@ammeraalbeltech.com  
www.ammeraalbeltech.com/fi

## France

T +33 3 20 90 36 00  
info-fr@ammeraalbeltech.com  
www.ammeraalbeltech.fr

## Germany

T +49 4152 937-0  
info-de@ammeraalbeltech.com  
www.ammeraalbeltech.de

## Hungary

T +36 30 311 6099  
info-hu@ammeraalbeltech.com  
www.ammeraalbeltech.hu

## India

T +91 44 265 34 244  
info-in@ammeraalbeltech.com  
www.ammeraalbeltech.com

## Italy

T +39 051 660 60 06  
info-it@ammeraalbeltech.com  
www.ammeraalbeltech.com/it

## Luxembourg

T +352 26 48 38 56  
info-lu@ammeraalbeltech.com  
www.ammeraal-beltech.lu

## Malaysia

T +60 3 806 188 49  
info-my@ammeraalbeltech.com  
www.ammeraalbeltech.com

## Netherlands

T +31 72 57 51212  
info-nl@ammeraalbeltech.com  
www.ammeraalbeltech.com/nl

## Poland

T +48 32 44 77 179  
info-pl@ammeraalbeltech.com  
www.ammeraalbeltech.com

## Portugal

T +351 22 947 94 40  
info-pt@ammeraalbeltech.com  
www.ammeraalbeltech.com/pt

## Singapore

T +65 62739767  
info-sg@ammeraalbeltech.com  
www.ammeraalbeltech.com/sg

## Slovakia

T +421 2 55648541-2  
info-sk@ammeraalbeltech.com  
www.ammeraalbeltech.sk

## South Korea

T +82 31 448 3613-7  
info-kr@ammeraalbeltech.com  
www.ammeraalbeltech.co.kr

## Spain

T +34 937 183 054  
info-es@ammeraalbeltech.com  
www.ammeraalbeltech.com/es

## Sweden

T +46 44 780 3010  
info-se@ammeraalbeltech.com  
www.ammeraalbeltech.se

## Switzerland

T +41 55 2253 535  
info-ch@ammeraalbeltech.com  
www.ammeraalbeltech.ch

## Thailand

T +66 2 902 2604-13  
info-th@ammeraalbeltech.com  
www.ammeraalbeltech.com

## United Kingdom

T +44 1992 500550  
info-uk@ammeraalbeltech.com  
www.ammeraalbeltech.com/uk

## United States

T +1 847 673 6720  
info-us@ammeraalbeltech.com  
www.ammeraalbeltech.com/us

## Vietnam

T +84 8 376 562 05  
info-vn@ammeraalbeltech.com  
www.ammeraalbeltech.com.vn

## Global Headquarters:

**Ammeraal Beltech Holding B.V.**  
P.O. Box 38  
1700 AA Heerhugowaard  
The Netherlands

T +31 (0)72 575 1212  
F +31 (0)72 571 6455

info@ammeraalbeltech.com  
www.ammeraalbeltech.com

**Expert advice, quality solutions  
and local service  
for all your belting needs**



Conveyor Belts




Timing Belts



Seamless Belts



Homogeneous Belts



Modular Belts



Fabrication & Service

... and 150 more service contact points at [www.ammeraalbeltech.com](http://www.ammeraalbeltech.com)