

# Endless Woven AmSqueeze Belts for Separating



Especially in the food industry products are being refined or recovered. In this industry some primary products such as carcasses, fat, meat, bones are separated with separator machines.

**Ammeraal Beltech offers a flexible squeezing belt for these heavy applications.**

#### **Typical industries**

- Meat & poultry
- Fish
- Fruit & vegetables
- Other industries: cheese, sausage, butter, tooth paste and chemicals

#### **Belt features**

- Rigid belt construction
- Easy to clean surface
- Wear resistant covers
- Different profiles available
- Food Grade (EC, FDA)

#### **Benefits**

- Non-cracking covers
- High yield
- Improved lifetime
- Less waste

# Innovation & Service in Belting

## Food Safety technology

A separating machine is designed to separate soft and solid components, e.g. meat from bones.

A separator belt transports product to a perforated drum and squeezes the softer material through the perforation. The harder particles remain outside the drum.




Diagram of the separating process

This continuous process ensures a smooth separation:

- » in the Meat Industry;
- » in the Fish Industry;
- » for fruit and vegetables processing: refining of juice and puree;
- » in waste disposal and recycling of e.g. cheese, sausage, butter, tooth paste, chemicals etc.

### Product benefits:

- Non-delaminating Food Grade belt covers on special designed endless woven fabric without seam.
- The topside of the belt is provided with profile A93 Rhombus for optimum grip and cleanability. Other profiles, e.g. A24 Herringbone, A18 Fine Square are available.
- The polyurethane belt covers ensure wear resistance and a long belt life.
- Completely sealed belt edges offer optimal hygiene conditions.
- Extended experience with belts for various brands of separator machinery.

## Example of Seamless Endless Woven Separator Belts

Belt type	AmSqueeze 300	AmSqueeze 500	AmSqueeze 700
<b>Example Article description</b>	AS 314 A93-A93	AS 514 A93-A93	AS 714 A93-A93
<b>Top cover material</b>	TPU 3 mm Ropanyl 76 (Shore A) FG	TPU 3 mm Ropanyl 85 (Shore A) FG	TPU 3 mm Ropanyl 93 (Shore A) FG
<b>Top cover color</b>	Ivory	White	Transparent
<b>Standard finish covers</b>	A93 Rhombus profile	A93 Rhombus profile	A93 Rhombus profile
<b>Standard belt thickness</b>	13,4 mm	13,4 mm	13,4 mm
<b>Other available belt thickness</b>	15,16,17,18,19,20 mm	15,16,17,18 mm	15,16,17,18 mm
<b>Grip</b>	+++++	++++	+++
<b>Wear resistance</b>	+++	++++	+++++
<b>Yield</b>	+++++	++++	+++
<b>Food Grade</b>	EC/FDA	EC/FDA	EC/FDA
<b>Indication application</b>	Soft	Medium	Hard
<b>Replaces</b>	Rubber	PU	PU hard

[Consult our application engineers and product information for other options](#) | [A questionnaire for belt selection is available](#)

**Tolerance on length ±1% Width -0/+2 mm | Closed edges skived**



**Expert advice and quality solutions for all your belting needs.**  
[ammeraalbeltech.com](http://ammeraalbeltech.com)

**Rydell Beltech**  
 51 Bazalgette Crescent  
 Dandenong South VIC 3175

This information is subject to alteration due to continuous development. Ammeraal Beltech will not be held liable for the incorrect use of the above stated information. This information replaces previous information. All activities performed and services rendered by Ammeraal Beltech are subject to general terms and conditions of sale and delivery, as applied by its operating companies.

Ph (03) 8780 6000  
[salesvic@rydell.com.au](mailto:salesvic@rydell.com.au)

[ammega.com](http://ammega.com)